(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 18 December 2003 (18.12.2003)

PCT

(10) International Publication Number WO 03/104171 A1

(51) International Patent Classification7: C07C 2/76, 9/06

(21) International Application Number: PCT/GB03/02426

(22) International Filing Date: 4 June 2003 (04.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0207066

10 June 2002 (10.06.2002) FR

(71) Applicant (for all designated States except US): BP CHEMICALS LIMITED [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): BASSET, Jean-Marie [FR/FR]; 18, Chemin J.B. Gilliard, F-69300 Caluire (FR). BRES, Philippe [FR/FR]; 2, allee Jules Marey, F-13500 Martigues (FR). COPERET, Christophe [FR/FR]; 136, avenue Thiers, F-69006 Lyon (FR). MAUNDERS, Barry, Martin [GB/GB]; "Woodlands", 5 Paddock Way, Woodham, Woking, Surrey GU21 5TB (GB). SOULIVONG, Daravong [FR/FR]; 8, Rue Turbil, F-69003 Lyon (FR). TAOUFIK, Mostafa [MA/FR]; 29, avenue Maurice Ravel, F-69140 Rillicux-la-Pape (FR). THIVOLLE-CAZAT, Jean [FR/FR]; 5, rue Gambetta, F-69270 Fontaines-sur-Saone (FR).
- (74) Agent: PREECE, Michael; BP International Limited, Patents & Agreements, Chertscy Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MÅ, MD, MG, MK, MN, MW, MX, MZ, NI, NO. NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM. ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR CONVERTING METHANE INTO ETHANE

(57) Abstract: The invention relates to a process for producing ethane comprising contacting methane with a metal catalyst selected from metal hydrides, metal organic compounds and mixtures thereof. It also relates to a process for the conversion of methane to carbon-containing products comprising contacting methane with a metal catalyst comprising at least one metal, Me, chosen from the lanthanides, the actinides and the metals from Groups 2 to 12 of the Periodic Table of the Elements, so as to produce ethane in a proportion of at least 65%, especially at least 98% or 99% by weight with respect to carbon-containing products formed in the process. The process can be a single-step process, preferably carried out under conditions involving a non-oxidative catalytic coupling of methane, in particular under operating conditions maintained substantially constant, preferably continuously, during the ethane production, e.g. at a temperature ranging from - 30°C to +80°C, preferably from 20°C to 500°C, under a total absolute pressure ranging from 10·3 to 100 MPa, preferably from 0.1 to 50 MPa. The metal catalyst may be chosen from metal catalysts supported on and preferably grafted to a solid support. One of the main advantages of the present invention is to produce ethane with a very high selectivity.